



Standard extruded heatsinks

<p>art. no.</p> <p>SK 65 ...</p>	<p>37,5 mm 5,5 K/W 75 mm 3,6 K/W</p> <p>for cases SOT 32</p>
<p>please indicate: ... 37.5 75 mm ... (optional) 1xM3, 2xM3</p>	
<p>art. no.</p> <p>SK 64 ...</p>	<p>37,5 mm 4,1 K/W 75 mm 2,7 K/W</p> <p>for cases TO 220, TOP 3</p>
<p>please indicate: ... 37.5 75 mm ... (optional) 1xM3, 2xM3</p>	
<p>art. no.</p> <p>SK 419 ...</p>	<p>1000 mm</p>
<p>art. no.</p> <p>SK 21 ...</p>	<p>with slots for cover plates or PCBs; mounting parts IS 1, IS 2, IS 3 → E 49</p>
<p>please indicate: ... 37.5 1000 mm ... (optional) TO 3, CB</p>	

Mounting for TO 3 angle
Order example
Special heatsink design
Heatsinks for DC/DC converter

→ A 125 Insulating clamping parts
→ A 21 Mica wafers
→ A 137 - 138 Insulator sleeves
→ A 113 - 114 Technical introduction

→ E 45
→ E 19
→ E 52
→ A 2 - 8