


# Bridge Rectifiers (Silicon) Single-Phase



Peak Reverse Voltage (PRV Volts)	IO, Average Rectified Forward Current (Amps)				
	1 A	1.5 A	2 A	4 A	
100			ECG166		
200			ECG167	ECG5309	ECG5318
400		ECG5304	ECG168		
600	ECG5332	ECG5305	ECG169	ECG5310	ECG5319
800		ECG5306			
1000	ECG5334	ECG5307	ECG170	ECG5311	ECG5320
Peak Forward Surge Current (Amps)	50	50	60	250	200
Max. Forward Voltage Per. Element VF (Volts)	1.0	1.0	1.0	1.0	1.0
TA at Rated IO (°C) Max	+40	+25	+25	+40	+50
Fig. No.	Z21	Z22	Z23	Z23-1	Z68A

Peak Reverse Voltage (PRV Volts)	IO, Average Rectified Forward Current (Amps)					
	6 A	8 A	25 A	40 A	80 A	100 A
100		ECG5312				
200	ECG5329	ECG5313	ECG5322	ECG5340		
400		ECG5314	ECG5324			
600	ECG5330	ECG5315	ECG5326	ECG5342	ECG5346	ECG5348
800		ECG5316	ECG5327			
1000	ECG5331	ECG5317	ECG5328	ECG5344		
Peak Forward Surge Current (Amps)	200	125	300	400	800	1000
Max. Forward Voltage Per. Element VF (Volts)	1.0	1.2	1.2	1.1	1.6	1.4
TA at Rated IO (°C) Max	+40	+50	+60	+60	+85	+80
Fig. No.	Z68	Z24	Z25	Z65		