

74F382 4-Bit Arithmetic Logic Unit

General Description

The 'F382 performs three arithmetic and three logic operations on two 4-bit words, A and B. Two additional Select input codes force the Function outputs LOW or HIGH. An Overflow output is provided for convenience in two complement arithmetic. A Carry output is provided for ripple expansion. For high-speed expansion using a Carry Look-ahead Generator, refer to the 'F381 data sheet.


Features

- Performs six arithmetic and logic functions
- Selectable LOW (clear) and HIGH (preset) functions
- LOW input loading minimizes drive requirements
- Carry output for ripple expansion
- Overflow output for twos complement arithmetic


Commercial	Package Number	Package Description
74F382PC	N20A	20-Lead (0.300" Wide) Molded Dual-In-Line
74F382SC (Note 1)	M20B	20-Lead (0.300" Wide) Molded Small Outline, JEDEC
74F382SJ (Note 1)	M20D	20-Lead (0.300" Wide) Molded Small Outline, EIAJ

Note 1: Devices also available in 13" reel. Use suffix = SCX and SJX.

Logic Symbols




TL/F/9529-6



TL/F/9529-3

Connection Diagram



TL/F/9529-1

Unit Loading/Fan Out

Pin Names	Description	74F	
		U.L. HIGH/LOW	Input I_{IH}/I_{IL} Output I_{OH}/I_{OL}
A_0-A_3	A Operand Inputs	1.0/4.0	20 μ A/ -2.4 mA
B_0-B_3	B Operand Inputs	1.0/4.0	20 μ A/ -2.4 mA
S_0-S_2	Function Select Inputs	1.0/1.0	20 μ A/ -0.6 mA
C_n	Carry Input	1.0/5.0	20 μ A/ -3.0 mA
C_{n+4}	Carry Output	50/33.3	-1 mA/20 mA
OVR	Overflow Output	50/33.3	-1 mA/20 mA
F_0-F_3	Function Outputs	50/33.3	-1 mA/20 mA

Functional Description

Signals applied to the Select inputs S_0-S_2 determine the mode of operation, as indicated in the Function Select Table. An extensive listing of input and output levels is shown in the Truth Table. The circuit performs the arithmetic functions for either active HIGH or active LOW operands, with output levels in the same convention. In the Subtract operating modes, it is necessary to force a carry (HIGH for active HIGH operands, LOW for active LOW operands) into the C_n input of the least significant package. Ripple expansion is illustrated in Figure 1. The overflow output OVR is the Exclusive-OR of C_{n+3} and C_{n+4} ; a HIGH signal on OVR indicates overflow in twos complement operation. Typical delays for Figure 1 are given in Figure 2.

Function Select Table

Select			Operation
S_0	S_1	S_2	
L	L	L	Clear
H	L	L	B Minus A
L	H	L	A Minus B
H	H	L	A Plus B
L	L	H	$A \oplus B$
H	L	H	$A + B$
L	H	H	AB
H	H	H	Preset

H = HIGH Voltage Level
L = LOW Voltage Level




FIGURE 1. 16-Bit Ripply Carry ALU Expansion

TL/F/9529-5

Path Segment	Toward F	Output C_{n+4} , OVR
A_i or B_i to C_{n+4}	6.5 ns	6.5 ns
C_n to C_{n+4}	6.3 ns	6.3 ns
C_n to C_{n+4}	6.3 ns	6.3 ns
C_n to F	8.1 ns	—
C_n to C_{n+4} , OVR	—	8.0 ns
Total Delay	27.2 ns	27.1 ns


FIGURE 2. 16-Bit Delay Tabulation

Truth Table

Function	Inputs						Outputs					
	S ₀	S ₁	S ₂	C _n	A _n	B _n	F ₀	F ₁	F ₂	F ₃	OVR	C _{n+4}
CLEAR	L	L	L	L	X	X	L	L	L	L	H	H
				H	X	X	L	L	L	L	H	H
B MINUS A	H	L	L	L	L	L	H	H	H	H	L	L
				L	L	H	L	H	H	L	H	
				L	H	L	L	L	L	L	L	
				L	H	H	H	H	L	L	L	
				H	L	L	L	L	L	L	L	
				H	L	H	H	H	L	L	L	
				H	H	L	L	L	L	L	L	
				H	H	H	L	L	L	L	L	
A MINUS B	L	H	L	L	L	L	H	H	H	H	L	L
				L	L	H	L	L	L	L	L	
				L	H	L	L	H	H	L	H	
				L	H	H	H	H	H	L	L	
				H	L	L	L	L	L	L	H	
				H	L	H	H	L	L	L	L	
				H	H	L	L	H	H	L	H	
				H	H	H	L	L	L	L	H	
A PLUS B	H	H	L	L	L	L	L	L	L	L	L	L
				L	L	H	H	H	H	L	L	
				L	H	L	H	H	H	L	L	
				L	H	H	H	H	H	L	H	
				H	L	L	L	L	L	L	L	
				H	L	H	L	L	L	L	H	
				H	H	L	L	L	L	L	H	
A ⊕ B	L	L	H	X	L	L	L	L	L	L	L	L
				X	L	H	H	H	H	L	L	
				L	H	L	L	H	H	L	L	
				X	H	H	L	L	L	H	H	
				H	H	L	L	H	H	H	H	
A + B	H	L	H	X	L	L	L	L	L	L	L	L
				X	L	H	H	H	H	L	L	
				X	H	L	H	H	H	L	L	
				L	H	H	H	H	H	L	L	
				H	H	H	H	H	H	H	H	
AB	L	H	H	X	L	L	L	L	L	L	H	H
				X	L	H	L	L	L	L	L	
				X	H	L	L	L	L	H	H	
				L	H	H	H	H	H	L	L	
				H	H	H	H	H	H	H	H	
PRESET	H	H	H	X	L	L	H	H	H	H	L	L
				X	L	H	H	H	H	L	L	
				X	H	L	H	H	H	L	L	
				L	H	H	H	H	H	L	L	
				H	H	H	H	H	H	H	H	

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial

Logic Diagram



TL/F/9529-4

Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Ratings (Note 1)

Storage Temperature	-65°C to +150°C
Ambient Temperature under Bias	-55°C to +125°C
Junction Temperature under Bias	-55°C to +175°C
Plastic	-55°C to +150°C
V _{CC} Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30 mA to +5.0 mA
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	
Standard Output	-0.5V to V _{CC}
TRI-STATE® Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated I _{OL} (mA)

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	0°C to +70°C
Commercial	
Supply Voltage	+4.5V to +5.5V
Commercial	

DC Electrical Characteristics over Operating Temperature Range unless otherwise specified


Symbol	Parameter	74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage			0.8	V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage			-1.2	V	Min	I _{IN} = -18 mA
V _{OH}	Output HIGH Voltage	74F 10% V _{CC} 74F 5% V _{CC}	2.5 2.7		V	Min	I _{OH} = -1 mA I _{OH} = -1 mA
V _{OL}	Output LOW Voltage	74F 10% V _{CC}		0.5	V	Min	I _{OL} = 20 mA
I _{IH}	Input HIGH Current	74F		5.0	μA	Max	V _{IN} = 2.7V
I _{BVI}	Input HIGH Current Breakdown Test	74F		7.0	μA	Max	V _{IN} = 7.0V
I _{CEX}	Output HIGH Leakage Current	74F		50	μA	Max	V _{OUT} = V _{CC}
V _{ID}	Input Leakage Test	74F	4.75		V	0.0	I _{ID} = 1.9 μA All Other Pins Grounded
I _{OD}	Output Leakage Circuit Current	74F		3.75	μA	0.0	V _{IOD} = 150 mV All Other Pins Grounded
I _{IL}	Input LOW Current			-0.6 -2.4 -3.0	mA	Max	V _{IN} = 0.5V (S ₀ -S ₂) V _{IN} = 0.5V (A ₀ -A ₃ , B ₀ -B ₃) V _{IN} = 0.5V (C _n)
I _{OS}	Output Short-Circuit Current		-60	-150	mA	Max	V _{OUT} = 0V
I _{CC}	Power Supply Current		54	81	mA	Max	

AC Electrical Characteristics


Symbol	Parameter	74F			74F		Units
		T _A = +25°C V _{CC} = +5.0V C _L = 50 pF			T _A , V _{CC} = Com C _L = 50 pF		
		Min	Typ	Max	Min	Max	
t _{PLH} t _{PHL}	Propagation Delay C _n to F _i	3.0 2.5	8.1 5.7	12.0 8.0	3.0 2.5	13.0 9.0	ns
t _{PLH} t _{PHL}	Propagation Delay Any A or B to Any F	4.0 3.0	10.4 8.2	15.0 11.0	3.5 2.5	17.0 12.0	ns
t _{PLH} t _{PHL}	Propagation Delay S _i to F _i	6.5 4.0	11.0 8.2	20.5 15.0	5.5 4.0	21.5 17.5	ns
t _{PLH} t _{PHL}	Propagation Delay A _i or B _i to C _n + 4	3.5 3.5	6.0 6.5	8.5 9.0	3.5 3.5	11.0 10.5	ns
t _{PLH} t _{PHL}	Propagation Delay S _i to OVR or C _n + 4	7.0 5.0	12.5 9.0	16.5 12.0	7.0 5.0	17.5 14.5	ns
t _{PLH} t _{PHL}	Propagation Delay C _n to C _n + 4	2.5 3.5	5.6 6.3	8.0 9.0	2.0 2.0	9.0 10.0	ns
t _{PLH} t _{PHL}	Propagation Delay C _n to OVR	3.5 2.5	8.0 7.1	11.0 10.0	3.5 2.5	13.0 11.0	ns
t _{PLH} t _{PHL}	Propagation Delay A _i or B _i to OVR	7.0 3.0	11.5 8.0	15.5 10.5	7.0 3.0	16.5 11.5	ns

Ordering Information



The device number is used to form part of a simplified purchasing code where the package type and temperature range are defined as follows:



Physical Dimensions inches (millimeters)




**20-Lead (0.300" Wide) Molded Small Outline Package, JEDEC (S)
NS Package Number M20B**



**20-Lead (0.300" Wide) Molded Small Outline Package, EIAJ (SJ)
NS Package Number M20D**

Physical Dimensions inches (millimeters) (Continued)



N20A (REV G)

**20-Lead (0.300" Wide) Molded Dual-In-Line Package (P)
NS Package Number N20A**

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
1111 West Bardin Road
Arlington, TX 76017
Tel: 1(800) 272-9959
Fax: 1(800) 737-7018

National Semiconductor Europe
Fax: (+49) 0-180-530 85 86
Email: cnjwge@tevm2.nsc.com
Deutsch Tel: (+49) 0-180-530 85 85
English Tel: (+49) 0-180-532 78 32
Français Tel: (+49) 0-180-532 93 58
Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
19th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: (852) 2737-1600
Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
Tel: 81-043-299-2309
Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.