

74F524 8-Bit Registered Comparator

General Description

The 'F524 is an 8-bit bidirectional register with parallel input and output plus serial input and output progressing from LSB to MSB. All data inputs, serial and parallel, are loaded by the rising edge of the input clock. The device functions are controlled by two control lines (S_0 , S_1) to execute shift, load, hold and read out.

An 8-bit comparator examines the data stored in the registers and on the data bus. Three true-HIGH, open-collector outputs representing 'register equal to bus', 'register greater than bus' and 'register less than bus' are provided. These outputs can be disabled to the OFF state by the use of Status Enable (\overline{SE}). A mode control has also been provided

to allow two's complement as well as magnitude compare. Linking inputs are provided for expansion to longer words.



Features

- 8-Bit bidirectional register with bus-oriented input-output
- Independent serial input-output to register
- Register bus comparator with 'equal to', 'greater than' and 'less than' outputs
- Cascadable in groups of eight bits
- Open-collector comparator outputs for AND-wired expansion
- Two's complement or magnitude compare

Commercial	Package Number	Package Description
74F524PC	N20A	20-Lead (0.300" Wide) Molded Dual-In-Line
74F524SC (Note 1)	M20B	20-Lead (0.300" Wide) Molded Small Outline, JEDEC


Note 1: Devices also available in 13" reel. Use suffix = SCX.

Logic Symbols



Connection Diagram

Pin Assignment for DIP and SOIC



Unit Loading/Fan Out

Pin Names	Description	74F	
		U.L. HIGH/LOW	Input I _{IH} /I _{IL} Output I _{OH} /I _{OL}
S ₀ , S ₁	Mode Select Inputs	1.0/1.0	20 μA/ -0.6 mA
C/SI	Status Priority or Serial Data Input	1.0/1.0	20 μA/ -0.6 mA
CP	Clock Pulse Input (Active Rising Edge)	1.0/1.0	20 μA/ -0.6 mA
\overline{SE}	Status Enable Input (Active LOW)	1.0/1.0	20 μA/ -0.6 mA
M	Compare Mode Select Input	1.0/1.0	20 μA/ -0.6 mA
I/O ₀ -I/O ₇	Parallel Data Inputs or TRI-STATE® Parallel Data Outputs	3.5/1.083 150/40 (33.3)	70 μA/ -0.65 mA -3 mA/24 mA (20 mA)
C/SO	Status Priority or Serial Data Output	50/33.3	-1 mA/20 mA
LT	Register Less Than Bus Output	OC*/33.3	*/20 mA
EQ	Register Equal Bus Output	OC*/33.3	*/20 mA
GT	Register Greater Than Bus Output	OC*/33.3	*/20 mA

*OC = Open Collector

Functional Description

The 'F524 contains eight D-type flip-flops connected as a shift register with provision for either parallel or serial loading. Parallel data may be read from or loaded into the registers via the data bus I/O₀-I/O₇. Serial data is entered from the C/SI input and may be shifted into the register and out through the C/SO output. Both parallel and serial data entry occur on the rising edge of the input clock (CP). The operation of the shift register is controlled by two signals S₀ and S₁ according to the Select Truth Table. The TRI-STATE parallel output buffers are enabled only in the Read mode.

One port of an 8-bit comparator is attached to the data bus while the other port is tied to the outputs of the internal register. Three active-OFF, open-collector outputs indicate whether the contents held in the shift register are 'greater than', (GT), 'less than' (LT), or 'equal to' (EQ) the data on the input bus. A HIGH signal on the Status Enable (\overline{SE}) input disables these outputs to the OFF state. A mode control input (M) allows selection between a straightforward magnitude compare or a comparison between twos complement numbers.

For 'greater than' or 'less than' detection, the C/SI input must be held HIGH, as indicated in the Status Truth Table. The internal logic is arranged such that a LOW signal on the C/SI input disables the 'greater than' and 'less than' outputs. The C/SO output will be forced HIGH if the 'equal to' status condition exists, otherwise C/SO will be held LOW. These facilities enable the 'F524 to be cascaded for word length greater than eight bits.

Word length expansion (in groups of eight bits) can be achieved by connecting the C/SO output of the more significant byte to the C/SI input of the next less significant byte and also to its own \overline{SE} input (see *Figure 1*). The C/SI input of the most significant device is held HIGH while the \overline{SE} input of the least significant device is held LOW. The corresponding status outputs are AND-wired together. In the case of twos complement number compare, only the Mode input to the most significant device should be HIGH. The Mode inputs to all other cascaded devices are held LOW.


Suppose that an inequality condition is detected in the most significant device. Assuming that the byte stored in the register is greater than the byte on the data bus, the EQ and LT outputs will be pulled LOW and the GT output will float HIGH. Also the C/SO output of the most significant device will be forced LOW, disabling the subsequent devices but enabling its own status outputs. The correct status condition is thus indicated. The same applies if the registered byte is less than the data byte, only in this case the EQ and GT outputs go LOW and LT output floats HIGH.

If an equality condition is detected in the most significant device, its C/SO output is forced HIGH. This enables the next less significant device and also disables its own status outputs. In this way, the status output priority is handed down to the next less significant device which now effectively becomes the most significant byte. The worst case propagation delay for a compare operation involving 'n' cascaded 'F524s will be when an equality condition is detected in all but the least significant byte. In this case, the status priority has to ripple all the way down the chain before the correct status output is established. Typically, this will take $35 + 6(n-2)$ ns.

Select Truth Table

S ₀	S ₁	Operation
L	L	Hold—Retains Data in Shift Register
L	H	Read—Read Contents in Register onto Data Bus, Data Remains in Register Unaffected by Clock
H	L	Shift—Allows Serial Shifting on Next Rising Clock Edge
H	H	Load—Load Data on Bus into Register

Block Diagram



TL/F/9546-5

Notes:

1. TRI-STATE Output
2. Open-Collector Output

Absolute Maximum Ratings (Note 1)

Storage Temperature	-65°C to +150°C
Ambient Temperature under Bias	-55°C to +125°C
Junction Temperature under Bias	-55°C to +175°C
Plastic	-55°C to +150°C
V _{CC} Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30 mA to +5.0 mA
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	
Standard Output	-0.5V to V _{CC}
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated I _{OL} (mA)

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	0°C to +70°C
Commercial	
Supply Voltage	+4.5V to +5.5V
Commercial	

DC Electrical Characteristics

Symbol	Parameter	74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage			0.8	V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage			-1.2	V	Min	I _{IN} = -18 mA
V _{OH}	Output HIGH Voltage	74F 10% V _{CC}	2.5		V	Min	I _{OH} = -1 mA I _{OH} = -3 mA I _{OH} = -1 mA I _{OH} = -3 mA
		74F 10% V _{CC}	2.4				
		74F 5% V _{CC}	2.7				
		74F 5% V _{CC}	2.7				
V _{OL}	Output LOW Voltage	74F 10% V _{CC}		0.5	V	Min	I _{OL} = 20 mA (I/O _n) I _{OL} = 24 mA (LT, GT, EQ, C/SO)
		74F 10% V _{CC}		0.5			
I _{IH}	Input HIGH Current	74F		5.0	μA	Max	V _{IN} = 2.7V
I _{BVI}	Input HIGH Current Breakdown Test	74F		7.0	μA	Max	V _{IN} = 7.0V
I _{CEX}	Output HIGH Leakage Current	74F		50	μA	Max	V _{OUT} = V _{CC} (I/O _n , C/SO)
V _{ID}	Input Leakage Test	74F	4.75		V	0.0	I _{ID} = 1.9 μA All Other Pins Grounded
I _{OD}	Output Leakage Circuit Current	74F		3.75	μA	0.0	V _{IOD} = 150 mV All Other Pins Grounded
I _{IL}	Input LOW Current			-0.6	mA	Max	V _{IN} = 0.5V
I _{IH} + I _{OZH}	Output Leakage Current			70	μA	Max	V _{I/O} = 2.7V
I _{IL} + I _{OZL}	Output Leakage Current			-650	μA	Max	V _{I/O} = 0.5V
I _{OS}	Output Short-Circuit Current			-60	mA	Max	V _{OUT} = 0V

DC Electrical Characteristics (Continued)

Symbol	Parameter	74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
I _{OHC}	Open Collector, Output OFF Leakage Test			250	μA	Min	V _{OUT} = V _{CC}
I _{CCH}	Power Supply Current		128	180	mA	Max	V _O = HIGH
I _{CCL}	Power Supply Current		128	180	mA	Max	V _O = LOW
I _{CCZ}	Power Supply Current		128	180	mA	Max	V _O = HIGH Z

AC Electrical Characteristics

Symbol	Parameter	74F			74F		Units
		T _A = +25°C V _{CC} = +5.0V C _L = 50 pF			T _A , V _{CC} = Com C _L = 50 pF		
		Min	Typ	Max	Min	Max	
f _{max}	Maximum Shift Frequency	50	75		50		MHz
t _{PLH} t _{PHL}	Propagation Delay I/O _n to EQ	9.0 5.0	16.5 9.5	20.0 12.0	9.0 5.0	21.0 13.0	ns
t _{PLH} t _{PHL}	Propagation Delay I/O _n to GT	8.5 6.5	14.1 13.0	19.0 16.5	8.5 6.5	20.0 17.5	
t _{PLH} t _{PHL}	Propagation Delay I/O _n to LT	7.0 4.5	15.5 10.0	20.0 14.0	7.0 4.5	21.0 15.0	
t _{PLH} t _{PHL}	Propagation Delay I/O _n to C/SO	8.0 6.0	15.2 12.5	19.5 16.0	8.0 6.0	20.5 17.0	ns
t _{PLH} t _{PHL}	Propagation Delay CP to EQ	10.0 4.0	20.0 8.5	25.0 16.5	10.0 4.0	26.0 17.5	ns
t _{PLH} t _{PHL}	Propagation Delay CP to GT	10.0 8.5	16.5 17.0	21.0 22.0	10.0 8.5	22.0 23.0	
t _{PLH} t _{PHL}	Propagation Delay CP to LT	9.0 5.5	20.0 13.5	25.0 17.0	9.0 5.5	26.0 18.0	
t _{PLH}	Propagation Delay CP to C/SO (Load)	8.5	16.5	21.0	8.5	22.0	ns
t _{PLH} t _{PHL}	Propagation Delay CP to C/SO (Serial Shift)	5.0 4.5	10.0 9.0	13.0 11.5	5.0 4.5	14.0 12.5	ns
t _{PLH} t _{PHL}	Propagation Delay C/SI to GT	9.0 3.0	15.0 6.5	19.0 8.5	9.0 3.0	20.0 9.5	
t _{PLH} t _{PHL}	Propagation Delay C/SI to LT	8.0 3.5	15.5 6.5	20.0 8.5	8.0 3.5	21.0 9.5	
t _{PLH} t _{PHL}	Propagation Delay S ₀ , S ₁ to C/SO	6.5 5.5	11.5 14.0	14.5 18.0	6.5 5.5	15.5 19.0	ns
t _{PLH} t _{PHL}	Propagation Delay SE to EQ	3.5 2.5	8.0 6.0	10.5 8.0	3.5 2.5	11.5 9.0	ns
t _{PLH} t _{PHL}	Propagation Delay SE to GT	6.5 3.5	12.5 6.0	16.0 8.0	6.5 3.5	17.0 9.0	
t _{PLH} t _{PHL}	Propagation Delay SE to LT	5.0 3.5	10.5 6.0	13.5 8.0	5.0 3.5	14.5 9.0	
t _{PLH} t _{PHL}	Propagation Delay C/SI to C/SO	4.0 4.0	8.5 8.5	11.0 11.0	4.0 4.0	12.0 12.0	ns

AC Electrical Characteristics


Symbol	Parameter	74F			74F		Units
		$T_A = +25^\circ\text{C}$ $V_{CC} = +5.0\text{V}$ $C_L = 50\text{ pF}$			$T_A, V_{CC} = \text{Com}$ $C_L = 50\text{ pF}$		
		Min	Typ	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay M to GT	8.0 6.0	15.0 12.0	19.5 17.5	8.0 6.0	20.5 18.5	ns
t_{PLH} t_{PHL}	Propagation Delay M to LT	8.0 4.5	17.0 9.5	22.0 12.0	8.0 4.5	23.0 13.0	
t_{PLH} t_{PHL}	Propagation Delay S_0, S_1 to EQ	15.0 9.0	25.0 15.0	33.0 19.0	15.0 9.0	35.0 20.0	ns
t_{PLH} t_{PHL}	Propagation Delay S_0, S_1 to GT	10.5 10.5	18.0 18.0	23.0 23.0	10.5 10.5	24.0 24.0	
t_{PLH} t_{PHL}	Propagation Delay S_0, S_1 to LT	13.0 12.0	22.0 19.0	28.0 24.0	13.0 12.0	30.0 25.0	
t_{PZH} t_{PZL}	Output Enable Time S_0, S_1 to I/O_n	4.5 5.5	10.0 11.0	13.0 15.0	4.5 5.5	14.0 16.0	ns
t_{PHZ} t_{PLZ}	Output Disable Time S_0, S_1 to I/O_n	3.5 4.5	8.0 9.6	12.0 12.5	3.5 4.5	13.0 13.5	

AC Operating Requirements

Symbol	Parameter	74F		74F		Units
		$T_A = +25^\circ\text{C}$ $V_{CC} = +5.0\text{V}$		$T_A, V_{CC} = \text{Com}$		
		Min	Max	Min	Max	
$t_s(H)$ $t_s(L)$	Setup Time, HIGH or LOW I/O_n to CP	6.0 6.0		6.0 6.0		ns
$t_h(H)$ $t_h(L)$	Hold Time, HIGH or LOW I/O_n to CP	0 0		0 0		
$t_s(H)$ $t_s(L)$	Setup Time, HIGH or LOW S_0 or S_1 to CP	10.0 10.0		10.0 10.0		ns
$t_h(H)$ $t_h(L)$	Hold Time, HIGH or LOW S_0 or S_1 to CP	0 0		0 0		
$t_s(H)$ $t_s(L)$	Setup Time, HIGH or LOW C/SI to CP	7.0 7.0		7.0 7.0		ns
$t_h(H)$ $t_h(L)$	Hold Time, HIGH or LOW C/SI to CP	0 0		0 0		
$t_w(H)$	Clock Pulse Width, HIGH	5.0		5.0		ns


Ordering Information

The device number is used to form part of a simplified purchasing code where the package type and temperature range are defined as follows:






Physical Dimensions inches (millimeters)



**20-Lead (0.300" Wide) Molded Small Outline Package, JEDEC
NS Package Number M20B**

M20B (REV. F)

Physical Dimensions inches (millimeters) (Continued)



**20-Lead (0.300" Wide) Molded Dual-In-Line Package (P)
NS Package Number N20A**

N20A (REV G)

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
1111 West Bardin Road
Arlington, TX 76017
Tel: 1(800) 272-9959
Fax: 1(800) 737-7018

National Semiconductor Europe
Fax: (+49) 0-180-530 85 86
Email: cnjwge@tevm2.nsc.com
Deutsch Tel: (+49) 0-180-530 85 85
English Tel: (+49) 0-180-532 78 32
Français Tel: (+49) 0-180-532 93 58
Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
19th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: (852) 2737-1600
Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
Tel: 81-043-299-2309
Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.