


# SN54HCT620, SN54HCT623, SN74HCT620, SN74HCT623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

D2804, MARCH 1984—REVISED SEPTEMBER 1987

- Inputs are TTL-Voltage Compatible
- Lock Bus-Latch Capability
- Choice of True or Inverting Logic
- High-Current 3-State Outputs Can Drive Up to 15 LSTTL Loads
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

DEVICE	LOGIC
'HCT620	Inverting
'HCT623	True


**SN54HCT'...J PACKAGE**  
**SN74HCT'...DW or N PACKAGE**  
(TOP VIEW)



2

HC MOS Devices

**SN54HCT'...FK PACKAGE**  
(TOP VIEW)



## description

These octal bus transceivers are designed for asynchronous two-way communication between data buses. The control function implementation allows for maximum flexibility in timing.

These devices allow data transmission from the A bus to the B bus or from the B bus to the A bus depending upon the logic levels at the enable inputs (GBA and GAB.)

The enable inputs can be used to disable the device so that the buses are effectively isolated.

The dual-enable configuration gives these devices the capability to store data by simultaneous enabling of GBA and GAB. Each output reinforces its input in this transceiver configuration. Thus when both control inputs are enabled and all other data sources to the two sets of bus lines are at high impedance, both sets of bus lines (16 in all) will remain at their last states. The 8-bit codes appearing on the two sets of buses will be identical for the 'HCT623 or complementary for the 'HCT620.

The SN54HCT620 and SN54HCT623 are characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74HCT620 and SN74HCT623 are characterized for operation from  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

## FUNCTION TABLE

ENABLE INPUTS		OPERATION	
GBA	GAB	'HCT620	'HCT623
L	L	$\bar{B}$ data to A bus	B data to A bus
H	H	$\bar{A}$ data to B bus	A data to B bus
H	L	Isolation	Isolation
L	H	$\bar{B}$ data to A bus, $\bar{A}$ data to B bus	B data to A bus, A data to B bus

**PRODUCTION DATA** documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1984, Texas Instruments Incorporated




POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

2-543


# SN54HCT620, SN54HCT623, SN74HCT620, SN74HCT620 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

logic symbols<sup>†</sup>



<sup>†</sup>These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic diagrams (positive logic)



# SN54HCT620, SN54HCT623, SN74HCT620, SN74HCT623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

## absolute maximum ratings over operating free-air temperature range<sup>†</sup>

Supply voltage, V <sub>CC</sub> . . . . .	-0.5 V to 7 V
Input clamp current, I <sub>IK</sub> (V <sub>I</sub> < 0 or V <sub>I</sub> > V <sub>CC</sub> ) . . . . .	±20 mA
Output clamp current, I <sub>OK</sub> (V <sub>O</sub> < 0 or V <sub>O</sub> > V <sub>CC</sub> ) . . . . .	±20 mA
Continuous output current, I <sub>O</sub> (V <sub>O</sub> = 0 to V <sub>CC</sub> ) . . . . .	±35 mA
Continuous current through V <sub>CC</sub> or GND pins . . . . .	±70 mA
Lead temperature 1.6 mm (1/16 in) from case for 60 s: FK or J package . . . . .	300°C
Lead temperature 1.6 mm (1/16 in) from case for 10 s: DW or N package . . . . .	260°C
Storage temperature range . . . . .	-65°C to 150°C

<sup>†</sup> Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

2

HCMOS Devices

## recommended operating conditions

		SN54HCT620			SN74HCT620			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V <sub>CC</sub>	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V <sub>IH</sub>	High-level input voltage	V <sub>CC</sub> = 4.5 V to 5.5 V	2		2			V
V <sub>IL</sub>	Low-level input voltage	V <sub>CC</sub> = 4.5 V to 5.5 V	0	0.8	0	0.8		V
V <sub>I</sub>	Input voltage		0	V <sub>CC</sub>	0	0	V <sub>CC</sub>	V
V <sub>O</sub>	Output voltage		0	V <sub>CC</sub>	0	0	V <sub>CC</sub>	V
t <sub>t</sub>	Input transition (rise and fall) times		0	500	0	0	500	ns
T <sub>A</sub>	Operating free-air temperature	-55	125	-40	85			°C

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	V <sub>CC</sub>	T <sub>A</sub> = 25°C			SN54HCT620		SN74HCT620		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V <sub>OH</sub>	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> , I <sub>OH</sub> = -20 $\mu$ A	4.5 V	4.4	4.499		4.4		4.4		V
	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> , I <sub>OH</sub> = -6 mA	4.5 V	3.98	4.30		3.7		3.84		
V <sub>OL</sub>	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> , I <sub>OL</sub> = 20 $\mu$ A	4.5 V		0.001	0.1	0.1		0.1		V
	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> , I <sub>OL</sub> = 6 mA	4.5 V		0.17	0.26	0.4		0.33		
I <sub>I</sub>	GAB or GBA	V <sub>I</sub> = V <sub>CC</sub> or 0	5.5 V	±0.1	±100	±1000		±1000		nA
I <sub>OZ</sub>	A or B	V <sub>I</sub> = V <sub>CC</sub> or GND	5.5 V	±0.01	±0.5	±10		±5		$\mu$ A
I <sub>CC</sub>		V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0	5.5 V		8	160		80		$\mu$ A
$\Delta I_{CC}^{\ddagger}$		One input at 0.5 V or 2.4 V Other inputs at 0 V or V <sub>CC</sub>	5.5 V	1.4	2.4	3.0		2.9		mA
C <sub>i</sub>	GAB or GBA		4.5 to 5.5 V	3	10	10		10		pF

<sup>†</sup>This is the increase in supply current for each input that is at one of the specified TTL voltage levels rather than 0 V or V<sub>CC</sub>.



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

# SN54HCT620, SN54HCT623, SN74HCT620, SN74HCT623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

2

HCMOS Devices

switching characteristics over recommended operating free-air temperature range (unless otherwise noted),  $C_L = 50 \text{ pF}$  (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V <sub>CC</sub>	$T_A = 25^\circ\text{C}$			SN54HCT620		SN74HCT620		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
$t_{pd}$	A or B	B or A	4.5 V	15	22	33	28	ns	ns	ns	
			5.5 V	13	20	30	25				
$t_{en}$	$\overline{\text{G}}\text{BA}$	A	4.5 V	30	42	63	53	ns	ns	ns	
			5.5 V	23	38	57	48				
$t_{dis}$	$\overline{\text{G}}\text{BA}$	A	4.5 V	18	30	45	38	ns	ns	ns	
			5.5 V	16	28	42	35				
$t_{en}$	GAB	B	4.5 V	30	42	63	53	ns	ns	ns	
			5.5 V	23	38	57	48				
$t_{dis}$	GAB	B	4.5 V	18	30	45	38	ns	ns	ns	
			5.5 V	16	28	42	35				
$t_t$		A or B	4.5 V	9	12	18	15	ns	ns	ns	
			5.5 V	8	11	16	14				
$C_{pd}$		Power dissipation capacitance per transceiver				No load, $T_A = 25^\circ\text{C}$	40 pF typ				

switching characteristics over recommended operating free-air temperature range (unless otherwise noted),  $C_L = 150 \text{ pF}$  (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V <sub>CC</sub>	$T_A = 25^\circ\text{C}$			SN54HCT620		SN74HCT620		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
$t_{pd}$	A or B	B or A	4.5 V	18	38	58	47	ns	ns	ns	
			5.5 V	11	34	52	42				
$t_{en}$	$\overline{\text{G}}\text{BA}$	A	4.5 V	36	59	89	74	ns	ns	ns	
			5.5 V	30	53	80	67				
$t_{en}$	GAB	B	4.5 V	36	59	89	74	ns	ns	ns	
			5.5 V	30	53	80	67				
$t_t$		A or B	4.5 V	17	42	63	53	ns	ns	ns	
			5.5 V	14	38	57	48				

NOTE 1: Load circuits and voltage waveforms are shown in Section 1.