

Lamps with metal bases for cars




Product benefits


- Wide product range
- Reliable quality

Product features


- Original spare parts



Product line drawing




Product line drawing




Product line drawing


Product family datasheet




Product line drawing




Product line drawing




Product line drawing




Product line drawing




Product line drawing



Base



Base



Base

Product family datasheet

Technical data

Product description	Nominal wattage	Nominal voltage	Base (standard designation)	Lifespan B3	Lifespan Tc	Length
64137L	21 W	12 V	BAW9s	400 h	700 h	38.9 mm
64136	21 W	12 V	BAY9s	300 h	600 h	38.9 mm
64132	6 W	12 V	BAX9s	350 h	700 h	33.0 mm
7225	21/4 W	12 V	BAZ15d	180 / 1250 h ²⁾	290 / 4000 h ²⁾	52.0 mm
7528	21/5 W	12 V	BAY15d	180 / 1250 h ²⁾	290 / 4000 h ²⁾	52.5 mm
7506	21 W	12 V	BA15s	250 h	500 h	52.5 mm
7507 ¹⁾	21 W	12 V	BAU15s	250 h	500 h	52.6 mm
5008	10 W	12 V	BA15s	350 h	800 h	37.5 mm
5007	5 W	12 V	BA15s	350 h	800 h	37.5 mm
5009 ¹⁾	10 W	12 V	BAU15s	350 h	800 h	37.5 mm
3893	4 W	12 V	BA9s	600 h	1200 h	27.4 mm
3796	2 W	12 V	BA9s	300 h	750 h	23.9 mm
3860	5 W	12 V	BA9s	400 h	1000 h	27.4 mm
7240	21 W	12 V	BA15d			52.5 mm

Product description	Diameter	New article	Test voltage	ECE category	Power input	Luminous flux
64137L	9.0 mm	NEW	13.5 V			
64136	9.0 mm		13.5 V	H21W	25 W	600 lm
64132	9.0 mm		13.5 V	H6W	7 W	125 lm

Product family datasheet

Product description	Diameter	New article	Test voltage	ECE category	Power input	Luminous flux
7225	25.0 mm		13.5 / 13.5 V	P21/4W	25 / 5 W	440/15 lm
7528	26.5 mm		13.5 / 13.5 V	P21/5W	25 / 6 W	440/35 lm
7506	26.5 mm		13.5 V	P21W	25 W	460 lm
7507 ¹⁾	25.0 mm		13.5 V	PY21W	25 W	280 lm
5008	19.0 mm		13.5 V	R10W	10 W	125 lm
5007	19.0 mm		13.5 V	R5W	5 W	50 lm
5009 ¹⁾	16.0 mm		13.5 V	RY10W	10 W	75 lm
3893	8.8 mm		13.5 V	T4W	4 W	35 lm
3796	9.0 mm		13.5 V	-	2 W	12.5 lm
3860	9.0 mm		13.5 V	-	5 W	50 lm
7240	25.0 mm		13.5 V	-		

Product description	Luminous flux tolerance	Power input tolerance
64137L		
64136	±12 %	±5 %
64132	±12 %	±5 %
7225	±15 / ±20 %	±6 / ±10 %
7528	±15 / ±20 %	±6 / ±10 %
7506	±15 %	±6 %
7507 ¹⁾	±20 %	±6 %
5008	±20 %	±10 %
5007	±20 %	±10 %

Product family datasheet

Product description	Luminous flux tolerance	Power input tolerance
5009 ¹⁾	±20 %	±10 %
3893	±20 %	±10 %
3796	±25 %	±8 %
3860	±20 %	±15 %
7240		

¹⁾ Amber lamp for clear indicators

²⁾ Filament 1

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.