

BDX34, BDX34A, BDX34B, BDX34C, BDX34D PNP SILICON POWER DARLINGTONS

Copyright © 1997, Power Innovations Limited, UK

AUGUST 1993 - REVISED MARCH 1997

- **Designed for Complementary Use with BDX33, BDX33A, BDX33B, BDX33C and BDX33D**
- **70 W at 25°C Case Temperature**
- **10 A Continuous Collector Current**
- **Minimum h_{FE} of 750 at 3 V, 3 A**

TO-220 PACKAGE
(TOP VIEW)



Pin 2 is in electrical contact with the mounting base.

MDTRACA

absolute maximum ratings at 25°C case temperature (unless otherwise noted)

RATING		SYMBOL	VALUE	UNIT
Collector-base voltage ($I_E = 0$)	BDX34	V_{CBO}	-45	V
	BDX34A		-60	
	BDX34B		-80	
	BDX34C		-100	
	BDX34D		-120	
Collector-emitter voltage ($I_B = 0$)	BDX34	V_{CEO}	-45	V
	BDX34A		-60	
	BDX34B		-80	
	BDX34C		-100	
	BDX34D		-120	
Emitter-base voltage		V_{EBO}	-5	V
Continuous collector current		I_C	-10	A
Continuous base current		I_B	-0.3	A
Continuous device dissipation at (or below) 25°C case temperature (see Note 1)		P_{tot}	70	W
Continuous device dissipation at (or below) 25°C free air temperature (see Note 2)		P_{tot}	2	W
Operating free air temperature range		T_J	-65 to +150	°C
Storage temperature range		T_{stg}	-65 to +150	°C
Operating free-air temperature range		T_A	-65 to +150	°C

NOTES: 1. Derate linearly to 150°C case temperature at the rate of 0.56 W/°C.
2. Derate linearly to 150°C free air temperature at the rate of 16 mW/°C.

PRODUCT INFORMATION

Information is current as of publication date. Products conform to specifications in accordance with the terms of Power Innovations standard warranty. Production processing does not necessarily include testing of all parameters.

BDX34, BDX34A, BDX34B, BDX34C, BDX34D

PNP SILICON POWER DARLINGTONS

AUGUST 1993 - REVISED MARCH 1997

electrical characteristics at 25°C case temperature (unless otherwise noted)

PARAMETER	TEST CONDITIONS			MIN	TYP	MAX	UNIT	
$V_{(BR)CEO}$ Collector-emitter breakdown voltage	$I_C = -100 \text{ mA}$	$I_B = 0$ (see Note 3)	BDX34 BDX34A BDX34B BDX34C BDX34D	-45 -60 -80 -100 -120			V	
I_{CEO} Collector-emitter cut-off current	$V_{CE} = -30 \text{ V}$ $V_{CE} = -30 \text{ V}$ $V_{CE} = -40 \text{ V}$ $V_{CE} = -50 \text{ V}$ $V_{CE} = -60 \text{ V}$ $V_{CE} = -30 \text{ V}$ $V_{CE} = -30 \text{ V}$ $V_{CE} = -40 \text{ V}$ $V_{CE} = -50 \text{ V}$ $V_{CE} = -60 \text{ V}$	$I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$ $I_B = 0$	$T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$	BDX34 BDX34A BDX34B BDX34C BDX34D BDX34 BDX34A BDX34B BDX34C BDX34D			-0.5 -0.5 -0.5 -0.5 -0.5 -10 -10 -10 -10 -10	mA
I_{CBO} Collector cut-off current	$V_{CB} = -45 \text{ V}$ $V_{CB} = -60 \text{ V}$ $V_{CB} = -80 \text{ V}$ $V_{CB} = -100 \text{ V}$ $V_{CB} = -120 \text{ V}$ $V_{CB} = -45 \text{ V}$ $V_{CB} = -60 \text{ V}$ $V_{CB} = -80 \text{ V}$ $V_{CB} = -100 \text{ V}$ $V_{CB} = -120 \text{ V}$	$I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$ $I_E = 0$	$T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$ $T_C = 100^\circ\text{C}$	BDX34 BDX34A BDX34B BDX34C BDX34D BDX34 BDX34A BDX34B BDX34C BDX34D			-1 -1 -1 -1 -1 -5 -5 -5 -5 -5	mA
I_{EBO} Emitter cut-off current	$V_{EB} = -5 \text{ V}$	$I_C = 0$				-10	mA	
h_{FE} Forward current transfer ratio	$V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$	$I_C = -4 \text{ A}$ $I_C = -4 \text{ A}$ $I_C = -3 \text{ A}$ $I_C = -3 \text{ A}$ $I_C = -3 \text{ A}$	(see Notes 3 and 4)	BDX34 BDX34A BDX34B BDX34C BDX34D	750 750 750 750 750			
$V_{BE(on)}$ Base-emitter voltage	$V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$ $V_{CE} = -3 \text{ V}$	$I_C = -4 \text{ A}$ $I_C = -4 \text{ A}$ $I_C = -3 \text{ A}$ $I_C = -3 \text{ A}$ $I_C = -3 \text{ A}$	(see Notes 3 and 4)	BDX34 BDX34A BDX34B BDX34C BDX34D			-2.5 -2.5 -2.5 -2.5 -2.5	V
$V_{CE(sat)}$ Collector-emitter saturation voltage	$I_B = -8 \text{ mA}$ $I_B = -8 \text{ mA}$ $I_B = -6 \text{ mA}$ $I_B = -6 \text{ mA}$ $I_B = -6 \text{ mA}$	$I_C = -4 \text{ A}$ $I_C = -4 \text{ A}$ $I_C = -3 \text{ A}$ $I_C = -3 \text{ A}$ $I_C = -3 \text{ A}$	(see Notes 3 and 4)	BDX34 BDX34A BDX34B BDX34C BDX34D			-2.5 -2.5 -2.5 -2.5 -2.5	V
V_{EC} Parallel diode forward voltage	$I_E = -8 \text{ A}$	$I_B = 0$				-4	V	

NOTES: 3. These parameters must be measured using pulse techniques, $t_p = 300 \mu\text{s}$, duty cycle $\leq 2\%$.

4. These parameters must be measured using voltage-sensing contacts, separate from the current carrying contacts.

PRODUCT INFORMATION

BDX34, BDX34A, BDX34B, BDX34C, BDX34D PNP SILICON POWER DARLINGTONS

AUGUST 1993 - REVISED MARCH 1997

thermal characteristics

PARAMETER		MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction to case thermal resistance			1.78	°C/W
$R_{\theta JA}$	Junction to free air thermal resistance			62.5	°C/W

resistive-load-switching characteristics at 25°C case temperature




PARAMETER	TEST CONDITIONS †			MIN	TYP	MAX	UNIT
t_{on} Turn-on time	$I_C = -3\text{ A}$	$I_{B(on)} = -12\text{ mA}$	$I_{B(off)} = 12\text{ mA}$		1		μs
t_{off} Turn-off time	$V_{BE(off)} = 3.5\text{ V}$	$R_L = 10\ \Omega$	$t_p = 20\ \mu\text{s}, dc \leq 2\%$		5		μs

† Voltage and current values shown are nominal; exact values vary slightly with transistor parameters.

BDX34, BDX34A, BDX34B, BDX34C, BDX34D PNP SILICON POWER DARLINGTONS

AUGUST 1993 - REVISED MARCH 1997

TYPICAL CHARACTERISTICS



THERMAL INFORMATION

MAXIMUM POWER DISSIPATION
VS
CASE TEMPERATURE




Figure 4.

BDX34, BDX34A, BDX34B, BDX34C, BDX34D PNP SILICON POWER DARLINGTONS


AUGUST 1993 - REVISED MARCH 1997

MECHANICAL DATA

TO-220

3-pin plastic flange-mount package

This single-in-line package consists of a circuit mounted on a lead frame and encapsulated within a plastic compound. The compound will withstand soldering temperature with no deformation, and circuit performance characteristics will remain stable when operated in high humidity conditions. Leads require no additional cleaning or processing when used in soldered assembly.



- NOTES: A. The centre pin is in electrical contact with the mounting tab.
 B. Mounting tab corner profile according to package version.
 C. Typical fixing hole centre stand off height according to package version.
 Version 1, 18.0 mm. Version 2, 17.6 mm.

MDXXBE

PRODUCT INFORMATION

IMPORTANT NOTICE

Power Innovations Limited (PI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to verify, before placing orders, that the information being relied on is current.

PI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with PI's standard warranty. Testing and other quality control techniques are utilized to the extent PI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except as mandated by government requirements.

PI accepts no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor is any license, either express or implied, granted under any patent right, copyright, design right, or other intellectual property right of PI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.

PI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS.

Copyright © 1997, Power Innovations Limited