
ORIGINAL

Lamps with glass wedge bases




Product benefits

- Wide product range
- Reliable quality


Product features

- Original spare parts


Product family datasheet




Product line drawing




Product line drawing




Product line drawing




Product line drawing



Product line drawing



Product line drawing



Product line drawing



Product line drawing

Product family datasheet

Technical data

| Product description | Electrical data | | | | | Photometrical data | | Dimensions & weight |
|---------------------|-----------------|-----------------|-----------------|-----------------------|--------------|--------------------|-------------------------|---------------------|
| | Power input | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Luminous flux | Luminous flux tolerance | Length |
| 921 | 19.4 W | 12.0 V | 16.00 W | ±10 % | 13.5 V | 310 lm | ±20 % | 38.0 mm |
| 921NA | 19.4 W | 12.0 V | 16.00 W | ±10 % | 13.5 V | 190 lm | ±20 % | 38.1 mm |
| 2723 | 2.3 W | 12.0 V | 2.30 W | ±8 % | 13.5 V | 18.6 lm | ±20 % | 20.0 mm |
| 7515 | 25 / 6 W | 12.0 V | 21/5 W | ±6 / ±10 % | 13.5 V | 440/35 lm | ±15 / ±20 % | 47.5 mm |
| 7505 | 25 W | 12.0 V | 21.00 W | ±6 % | 13.5 V | 460 lm | ±15 % | 47.5 mm |
| 2821 | 3 W | 12.0 V | 3.00 W | ±10 % | 13.5 V | 22 lm | ±30 % | 26.8 mm |
| 2825 | 5 W | 12.0 V | 5.00 W | ±10 % | 13.5 V | 50 lm | ±20 % | 26.8 mm |
| 7504 ¹⁾ | 25 W | 12.0 V | 21.00 W | ±6 % | 13.5 V | 280 lm | ±20 % | 47.5 mm |
| 2827 ¹⁾ | 5 W | 12.0 V | 5.00 W | ±10 % | 13.5 V | 30 lm | ±20 % | 26.8 mm |
| 2721 | 1.22 W | 12.0 V | 1.20 W | ±15 % | 13.5 V | 7.5 lm | ±20 % | 20.0 mm |
| 2722 | 2 W | 12.0 V | 2.00 W | ±15 % | 13.5 V | 12 lm | ±20 % | 20.0 mm |
| 2820 | 2.2 W | 12.0 V | 2.00 W | ±10 % | 13.5 V | 13.5 lm | ±25 % | 26.8 mm |

| Product description | Diameter | Lifespan | | Additional product data | Certificates & standards | Country specific categorizations |
|---------------------|----------|---------------------------|----------------------------|-----------------------------|--------------------------|----------------------------------|
| | | Lifespan B3 | Lifespan Tc | Base (standard designation) | ECE category | Order reference |
| 921 | 16.0 mm | 400 h | 1000 h | W2.1x9.5d | W16W | 921-02B 16W 12V |
| 921NA | 16.0 mm | 400 h | 1000 h | W2.1x9.5d | WY16W | 921NA 16W 12V W |
| 2723 | 5 mm | 350 h | 1200 h | W2x4.6d | W2,3W | |
| 7515 | 20.0 mm | 250 / 600 h ²⁾ | 500 / 1600 h ²⁾ | W3x16q | W21/5W | 7515-02B 21/5W |
| 7505 | 20.0 mm | 400 h | 600 h | W3x16d | W21W | 7505-02B 21W 12 |
| 2821 | 10.3 mm | 1300 h | 4000 h | W2.1x9.5d | W3W | 2821 3W12VW2,1X |
| 2825 | 10.0 mm | 350 h | 1000 h | W2.1x9.5d | W5W | 2825 5W12VW2,1X |

Product family datasheet

| Product description | Diameter | Lifespan | | Additional product data | Certificates & standards | Country specific categorizations |
|---------------------|----------|-------------|-------------|-----------------------------|--------------------------|----------------------------------|
| | | Lifespan B3 | Lifespan Tc | Base (standard designation) | ECE category | Order reference |
| 7504 ¹⁾ | 20.0 mm | 400 h | 600 h | WX3x16d | WY21W | 7504 21W 12V WX |
| 2827 ¹⁾ | 10.0 mm | 350 h | 1000 h | W2.1x9.5d | WY5W | 2827 5W 12V W2. |
| 2721 | 5 mm | 500 h | 2000 h | W2x4.6d | - | 2721 1,2W12VW2X |
| 2722 | 5 mm | 1300 h | 4000 h | W2x4.6d | - | 2722 |
| 2820 | 10.0 mm | 600 h | 4000 h | W2.1x9.5d | - | 2820 |

¹⁾ Amber lamp for clear indicators

²⁾ Filament 1

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.