

Standard extruded heatsinks

<p>art. no.</p> <p>SK 04 ...</p>		
<p>with slots for cover plates or PCBs</p>		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 37.5 50 75 100 1000 mm ... $\left[\begin{array}{c} \circ \\ \circ \\ \circ \end{array} \right]$ (optional) SSR 1, SSR 2, TO 3, CB</p>		
<p>art. no.</p> <p>SK 403 ...</p>		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 1000 mm</p>		
<p>art. no.</p> <p>SK 73 ...</p>		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 50 75 1000 mm ... $\left[\begin{array}{c} \circ \\ \circ \\ \circ \end{array} \right]$ (optional) TO 3, CB</p>		
<p>art. no.</p> <p>SK 71 ...</p>		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 37.5 50 75 100 1000 mm ... $\left[\begin{array}{c} \circ \\ \circ \\ \circ \end{array} \right]$ (optional) TO 3</p>		
<p>art. no.</p> <p>SK 57 ...</p>		
<p>with slots for cover plates or PCBs</p>		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 37.5 75 100 1000 mm</p>		

B

C

D

E

F

G

H

I

K

L

M

Hole pattern → A 21
 Profiles for PCB components → A 91
 Heatsinks for PCB → A 89
 Profiles for PCB mounting → A 89 - 112

→ A 21 Screw mounted guide rails
 → A 91 Thermal conductive material
 → A 89 Heatsink-cooling aggregates
 → A 89 - 112 Technical introduction

→ E 26 - 27
 → E 2 - 24
 → D 14
 → A 2 - 8

A 64

N