



ELECTRONICS, INC.  
44 FARRAND STREET  
BLOOMFIELD, NJ 07003  
(973) 748-5089

## NTE7030 Integrated Circuit Module, AF PO, 50W, Dual Power Supply

### **Features:**

- Small-Sized Package Allows Audio Sets to be made Slimmer
- Facilitates Thermal Design of Slim Stereo Sets
- Constant-Current Circuit Minimizes Pop Noise During Power ON/OFF
- Possible to Design Electronic Supplementary Circuits:
  - Pop Noise Muting During Power ON/OFF
  - Load Short-Circuit Protector
  - Thermal Shutdown

### **Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Maximum Supply Voltage, $V_{CC\max}$ .....	$\pm 52\text{V}$
Junction Temperature, $T_J$ .....	$+150^\circ\text{C}$
Operating Case Temperature, $T_C$ .....	$+125^\circ\text{C}$
Storage Temperature Range, $T_{stg}$ .....	$-30^\circ \text{ to } +125^\circ\text{C}$
Thermal Resistance, Junction-to-Case, $R_{thJC}$ .....	$1.8^\circ\text{C/W}$
Available Time for Load Shorted ( $V_{CC} = \pm 35\text{V}$ , $R_L = 8\Omega$ , $f = 50\text{Hz}$ , $P_O = 50\text{W}$ ), $t_s$ .....	2sec

### **Recommended Operating Conditions:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Recommended Supply Voltage, $V_{CC}$ .....	$\pm 35\text{V}$
Load Resistance, $R_L$ .....	$8\Omega$

### **Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ , $V_{CC} = \pm 35\text{V}$ , $R_L = 8\Omega$ (Non-Inductive Load), $R_g = 600\Omega$ , $V_G = 40\text{dB}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	$I_{CC0}$	$V_{CC} = \pm 42\text{V}$	10	20	50	mA
Output Power	$P_O$	THD = 0.4%, $f = 20\text{Hz}$ to $20\text{kHz}$	50	—	—	W
		$V_{CC} = \pm 31\text{V}$ , THD = 1%, $R_L = 4\Omega$ , $f = 1\text{kHz}$	55	—	—	W
Total Harmonic Distortion	THD	$P_O = 1\text{W}$ , $f = 1\text{kHz}$	—	—	0.3	%
Frequency Response	$f_L, f_H$	$P_O = 1\text{W}$ +0dB, -3dB	20 to 50k			Hz
Input Resistance	$r_i$	$P_O = 1\text{W}$ , $f = 1\text{kHz}$	—	55	—	k $\Omega$
Output Noise Voltage	$V_{NO}$	$V_{CC} = \pm 42\text{V}$ , $R_g = 10\text{k}\Omega$ , Note 2	—	—	1.2	mV <sub>rms</sub>
Middle-Point Voltage	$V_N$	$V_{CC} = \pm 42\text{V}$	-70	0	+70	mV

Note 1. For power supply at the time of test, use a constant-voltage power supply unless otherwise specified.

Note 2. The output noise voltage represents the peak value on the RMS scale ( $V_{TMV}$ ) of average value indicating type. The noise voltage waveform includes no flicker noise.

**Pin Connection Diagram**  
(Front View)

<b>15</b>	Bootstrap
<b>14</b>	(+) V <sub>CC</sub>
<b>13</b>	Output
<b>12</b>	(-) V <sub>CC</sub>
<b>11</b>	Compensation
<b>10</b>	I Adjust
<b>9</b>	Emitter Bypass
<b>8</b>	Compensation
<b>7</b>	I Adjust
<b>6</b>	Test Point
<b>5</b>	Bypass
<b>4</b>	Bias
<b>3</b>	Substrate
<b>2</b>	NFB
<b>1</b>	Input

