



NTE713 Integrated Circuit Chroma Demod

Description:

The NTE713 is a monolithic integrated circuit in a 14-Lead DIP type package that contains two sets of synchronous detectors with matrix circuits to achieve the R-Y, G-Y, and B-Y color difference output signals. The chroma input signal is applied to Pin3 and Pin4 while the oscillator injection signal is applied to Pin6 and Pin7. The color difference signals, after matrix, have fixed a relationship of amplitude and phase nominally equal DC voltage levels. The outputs of the NTE713 are suitable for driving high level color difference or R, G, B output amplifiers. Emitter-follower output stages used to drive the high level color amplifiers have short-circuit protection.

Features:

- Synchronous Detector with Color Difference Matrix
- Emitter-Follower Output Amplifier with Short-Circuit Protection

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

DC Supply Voltage (Pin8 to Pin14)	27V
Reference Input Voltage	5V _{P-P}
Chroma Input Voltage	5V _{P-P}
Device Dissipation ($T_A \leq +70^\circ\text{C}$)	530mW
Derate Linearly Above 70°C	6.7mW/ $^\circ\text{C}$
Operating Ambient Temperature Range	-40° to +85°C
Storage Temperature Range	-65° to +150°C
Lead Temperature (During Soldering, 1/32" from seating plane, 10sec max)	+265°C

Electrical Characteristics: ($V_+ = 24\text{V}$, $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Static Characteristics							
Supply Current with Output Loads	I_T	S ₁ Closed		16.5	-	26.5	mA
		S ₁ Open		-	9	-	mA
G-Y, R-Y, B-Y Outputs	V_9, V_{11}, V_{13}	S ₁ Closed		13.2	14.7	15.8	V
Chroma Inputs	V_3, V_4	S ₁ Open		-	3.3	-	V
Reference Subcarrier	V_6, V_7	S ₁ Open		-	6.2	-	V

Electrical Characteristics (Cont'd): ($V_+ = 24V$, $T_A = +25^\circ C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Dynamic Characteristics						
Demodulator Unbalance	V_9, V_{11}, V_{13}	$V_3 = V_4 = 0$	—	—	0.8	V_{P-P}
Maximum Color Difference Output Voltage	V_{13}	$V_3 = V_4 = 0.6V_{P-P}$	8.0	—	—	V_{P-P}
	V_{11}		5.5	—	—	V_{P-P}
	V_9		1.2	—	—	V_{P-P}
Chroma Input Sensitivity	v_3	Adjust e_c for $5V_{P-P}$ @ Pin13 (B-Y)	—	0.2	0.35	V_{P-P}
Relative R-Y Output	v_{11}		3.5	—	4.2	V_{P-P}
Relative G-Y Output	v_9		0.75	—	1.25	V_{P-P}
V_{DC} Difference Between Any Two Output Pins	$ V_9 - V_{11} $ $ V_9 - V_{13} $ $ V_{11} - V_{13} $	$e_c = 0$	—	—	0.6	V
Input Impedance Reference Subcarrier Inputs	$r_i6, 7$	—	—	1.7	—	kΩ
Input Capacitance Reference Subcarrier Inputs	$c_i6, 7$	—	—	6	—	pF
Input Impedance at Chroma Inputs	$r_i3, 4$	—	—	0.95	—	kΩ
Input Capacitance at Chroma Inputs	$c_i3, 4$	—	—	5	—	pF
Output Resistance	$r_o9, r_o11,$ r_o13	—	—	180	—	W

Pin Connection Diagram

