Regulation EC No 1907/2006 Art.31

Productname:

Lub oil 88

Ref.Nr.:

BDS000712_3_20131003 (EN)

Creationdate : Replaces:

03.10.13 Version : 2.0

BDS000712_20111104

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lub oil 88

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe byba Touwslagerstraat 1 9240 Zele Belgium

Tel.: +32(0)52/45.60.11 Fax.: +32(0)52/45.00.34 E-mail: hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	+358/(19)383.676
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303.0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTR. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Kryptongatan 14, 431 53 Mölndal	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical:

Aerosols, category 1

Extremely flammable aerosol.



Regulation EC No 1907/2006 Art.31

Productname: Lub oil 88 Creationdate: 03.10.13 Version: 2.0 Ref.Nr.: BDS000712 3 20131003 (EN) Replaces: BDS000712 20111104

Pressurised container: May burst if heated.

Health: Not classified **Environment:** Not classified

Other hazards: Repeated exposure may cause skin dryness or cracking.

Classification according to 67/548/EEC or 1999/45/EC:

EXTREMELY FLAMMABLE

Health: R66: Repeated exposure may cause skin dryness or cracking.

Physical: **EXTREMELY FLAMMABLE**

Environment: Not classified

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s): H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Precautionary statement(s): P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

Supplemental Hazard

Repeated exposure may cause skin dryness or cracking. information:

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	(926-141-6)	25-50	Xn	65-66	В



Regulation EC No 1907/2006 Art.31

 Productname :
 Lub oil 88
 Creationdate :
 03.10.13 Version : 2.0

 Ref.Nr.:
 BDS000712_3_20131003 (EN)
 Replaces:
 BDS000712_20111104

carbon dioxide	124-38-9	204-696-9	1-5	-	-	A,G
Explanation notes						
A : substance with Community workplace exposure limit						
B : substance with national established workplace exposure limit						
G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006						

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	01-2119456620- 43	64742- 47-8	(926- 141-6)	25- 50	Asp. Tox. 1	H304	В
carbon dioxide		124-38-9	204-696- 9	1-5	Press. Gas	H280	A,G
Explanation notes							
A : substance with Community workplace exposure limit							
B : substance with national established workplace exposure limit							
G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006							

^{(*} Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	If substance has got into eyes, immediately wash out with plenty of water If eye irritation persists: Get medical advice/attention.
Contact with skin :	Wash with plenty of soap and water.
	If skin irritation occurs: Get medical advice/attention.
Inhalation :	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion :	If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms: sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause irritation. Symptoms : redness and pain
Eye contact :	May cause irritation. Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor



Regulation EC No 1907/2006 Art.31

Productname: Lub oil 88

Ref.Nr.: BDS000712_3_20131003 (EN)

Creationdate : Replaces:

03.10.13 Version : 2.0 BDS000712 20111104

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition Take precautionary measures against static discharges



Regulation EC No 1907/2006 Art.31

Productname:

Lub oil 88

Ref.Nr.:

BDS000712 3 20131003 (EN)

Creationdate:

03.10.13 Version: 2.0

Replaces:

BDS000712 20111104

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Lubricants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
carbon dioxide	124-38-9	TWA	5000 ppm
National established exposure limits, United Kingdom			
carbon dioxide	124-38-9	TWA	5000 ppm
		STEL	15000 ppm

8.2. Exposure controls

3	(`Antrol	procedures	
		procedures	
		•	

Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product. Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

Air purifying respirator equiped with organic gas/vapor cartridge (type A or

AX)

hands and skin: Wear suitable protective gloves against chemicals

(nitrile)

Wear safety goggles.

Environmental protection:

Avoid release to the environment.



eyes:

Regulation EC No 1907/2006 Art.31

Productname: Lub oil 88

Ref.Nr.: BDS000712_3_20131003 (EN)

Creationdate: 03.10.13 Version: 2.0 BDS000712 20111104

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant) **Apperance : physical state :** CO2 propelled liquid.

colour :Amber.odour :Solvent.

pH: Not applicable.

Boiling point/range: Not available.

Flash point: 70 °C (Closed Cup)

Evaporation rate: Not applicable.

Explosion limits: upper limit: Not available.

lower limit: Not available.

Vapour pressure: Not available.

Relative density: 0.825 g/cm3 (@ 20°C). **Solubility in water:** Insoluble in water

Auto-ignition : $> 200 \, ^{\circ}\text{C}$

Viscosity: 5 mPa.s (@ 20°C).

9.2. Other information

VOC: 350 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials



Regulation EC No 1907/2006 Art.31

Productname: Lub oil 88

Ref.Nr.: BDS000712_3_20131003 (EN)

Creationdate : Replaces:

03.10.13 Version : 2.0 BDS000712_20111104

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis Repeated exposure may cause skin dryness or cracking.

Eye contact : May cause irritation.

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	LD50 oral rat	> 5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential



Regulation EC No 1907/2006 Art.31

Productname: Lub oil 88

Ref.Nr.:

BDS000712_3_20131003 (EN)

Creationdate : Replaces:

03.10.13 Version : 2.0 BDS000712 20111104

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous:

IMDG - Marine pollutant: No



Regulation EC No 1907/2006 Art.31

 Productname :
 Lub oil 88
 Creationdate :
 03.10.13 Version : 2.0

 Ref.Nr.:
 BDS000712 3 20131003 (EN)
 Replaces:
 BDS000712 20111104

IATA/ICAO - Environmentally hazardous:

14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

Regulation (EC) No 1907/2006 (REACH)

EU-directive 99/45/EC

Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases: R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

*Explanation hazard statements: H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

REVISIONS IN CHAPTRE: 2.2. Label elements

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

