

SN54HC808, SN74HC808 HEX 2-INPUT AND DRIVERS

D2804, MARCH 1984—REVISED SEPTEMBER 1987

- High-Current Outputs Can Drive Up to 15 LSTTL Loads
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description


These devices contain six independent 2-input AND drivers. They perform the Boolean functions $Y = A \cdot B$ or $Y = \bar{A} + \bar{B}$ in positive logic.

The SN54HC808 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74HC808 is characterized for operation from -40°C to 85°C .

FUNCTION TABLE
(EACH DRIVER)


INPUTS		OUTPUT
A	B	Y
H	H	H
L	X	L
X	L	L

logic symbol[†]




[†]This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.


SN54HC808 . . . J PACKAGE
SN74HC808 . . . DW OR N PACKAGE
(TOP VIEW)



SN54HC808 . . . FK PACKAGE
(TOP VIEW)



logic diagram (positive logic)



2

HCMOS Devices

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1984, Texas Instruments Incorporated

TEXAS
INSTRUMENTS

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

2-605

SN54HC808, SN74HC808 HEX 2-INPUT AND DRIVERS

2

HCMOS Devices

absolute maximum ratings over operating free-air temperature range†

Supply voltage, V _{CC}	-0.5 V to 7 V
Input clamp current, I _{IK} (V _I < 0 or V _I > V _{CC})	±20 mA
Output clamp current, I _{OK} (V _O < 0 or V _O > V _{CC})	±20 mA
Continuous output current, I _O (V _O = 0 to V _{CC})	±35 mA
Continuous current through V _{CC} or GND pins	±70 mA
Lead temperature 1.6 mm (1/16 in) from case for 60 s: FK or J package	300°C
Lead temperature 1.6 mm (1/16 in) from case for 10 s: DW or N package	260°C
Storage temperature range	-65°C to 150°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

recommended operating conditions

		SN54HC808			SN74HC808			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage	2	5	6	2	5	6	V
V _{IH}	High-level input voltage	V _{CC} = 2 V V _{CC} = 4.5 V V _{CC} = 6 V	1.5 3.15 4.2		1.5 3.15 4.2			V
V _{IL}	Low-level input voltage	V _{CC} = 2 V V _{CC} = 4.5 V V _{CC} = 6 V	0 0 0	0.3 0.9 1.2	0 0 0	0.3 0.9 1.2		V
V _I	Input voltage		0	V _{CC}	0	V _{CC}	V _{CC}	V
V _O	Output voltage		0	V _{CC}	0	V _{CC}	V _{CC}	V
t _t	Input transition (rise and fall) times	V _{CC} = 2 V V _{CC} = 4.5 V V _{CC} = 6 V	0 0 0	1000 500 400	0 0 0	1000 500 400		ns
T _A	Operating free-air temperature		-55	125	-40	85	85	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	V _{CC}	T _A = 25°C			SN54HC808		SN74HC808		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V _{OH}	V _I = V _{IH} or V _{IL} , I _{OH} = -20 μA	2 V 4.5 V 6 V	1.9 4.4 5.9	1.998 4.499 5.999		1.9 4.4 5.9		1.9 4.4 5.9		V
	V _I = V _{IH} or V _{IL} , I _{OH} = -6 mA	4.5 V	3.98	4.30		3.7		3.84		
	V _I = V _{IH} or V _{IL} , I _{OH} = -7.8 mA	6 V	5.48	5.80		5.2		5.34		
V _{OL}	V _I = V _{IH} or V _{IL} , I _{OL} = 20 μA	2 V 4.5 V 6 V	0.002 0.001 0.001	0.1 0.1 0.1		0.1 0.1 0.1		0.1 0.1 0.1		V
	V _I = V _{IH} or V _{IL} , I _{OL} = 6 mA	4.5 V	0.17	0.26		0.4		0.33		
	V _I = V _{IH} or V _{IL} , I _{OL} = 7.8 mA	6 V	0.15	0.26		0.4		0.33		
I _I	V _I = V _{CC} or 0	6 V	±0.1	±100		±1000		±1000	nA	
I _{CC}	V _I = V _{CC} or 0, I _O = 0	6 V		8		160		80	μA	
C _i		2 to 6 V		3	10		10	10	pF	

**SN54HC808, SN74HC808
HEX 2-INPUT AND DRIVERS**

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $C_L = 50 \text{ pF}$ (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC}	T _A = 25°C			SN54HC808		SN74HC808		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t_{pd}	A or B	Y	2 V	50	100		150		125		ns
			4.5 V	10	20		30		25		
			6 V	8	17		25		21		
t_t		Y	2 V	28	60		90		75		ns
			4.5 V	8	12		18		15		
			6 V	6	10		15		13		
C_{pd}	Power dissipation capacitance per gate				No load, T _A = 25°C			20 pF typ			

Note 1: Load circuits and voltage waveforms are shown in Section 1.

2

HCMOS Devices