



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE853 Integrated Circuit Low Power, Narrow Band, FM IF System

Description:

The NTE853 is a low power narrow band FM IF system which includes: Oscillator, Mixer, Limiting Amplifier, Quadrature Discriminator, Active Filter, Squelch, Scan Control and Mute Switch. The NTE853 is designed for use in FM dual conversion communications equipment.

Features:

- Low Drain Current (3mA Typ @ $V_{CC} = 6V$)
- Excellent Sensitivity: Input Limiting Voltage (-3.0dB) = 5.0 μ V (Typ)
- Low Number of External Parts Required

Absolute Maximum Ratings: ($T_A = +25^\circ C$, unless otherwise specified)

Power Supply Voltage (Pin4), $V_{CC(max)}$	12V
Operating Supply Voltage Range (Pin4), V_{CC}	4V to 8V
Detector Input Voltage (Pin8),	1V _{p-p}
Input Voltage ($V_{CC} \geq 6V$, Pin16), V_{16}	1V _{RMS}
Mute Function (Pin14), V_{14}	-0.5V to 5V _{pk}
Operating Junction Temperature, T_J	+150°C
Operating Ambient Temperature Range, T_A	-30° to +70°C
Storage Temperature Range, T_{stg}	-65° to +150°C

Electrical Characteristics: ($V_{CC} = 6V$, $f_O = 10.7MHz$, $\Delta f = \pm 3kHz$, $f_{mod} = 1kHz$, $T_A = +25^\circ C$ unless otherwise specified)

Parameter	Pin	Test Conditions	Min	Typ	Max	Unit
Drain Current, Squelch OFF	4		-	2	-	mA
Drain Current, Squelch ON	4		-	3	5	mA
Input Limiting Voltage	16	-3dB Limiting	-	5	10	μ V
Detector Output Voltage	9		-	3	-	V
Detector Output Impedance	-		-	400	-	Ω
Recovered Audio Output Voltage	9	$V_{in} = 10mV$	200	350	-	mV _{rms}

Electrical Characteristics (Cont'd): ($V_{CC} = 6V$, $f_O = 10.7MHz$, $\Delta f = \pm 3kHz$, $f_{mod} = 1kHz$, $T_A = +25^\circ C$ unless otherwise specified)

Parameter	Pin	Test Conditions	Min	Typ	Max	Unit
Filter Gain	–	$V_{in} = 10mV$, 10kHz	40	46	–	dB
Filter Output Voltage	11		1.8	2.0	2.5	V
Trigger Hysteresis	–		–	100	–	mV
Mute Function, LOW	14		–	15	50	Ω
Mute Function, HIGH	14		1	10	–	$M\Omega$
Scan Function, LOW	13	Mute OFF, $V_{12} = 2V$	–	0	0.5	V
Scan Function, HIGH	13	Mute ON, $V_{12} = GND$	5.0	–	–	V
Mixer Conversion Gain	3		–	20	–	dB
Mixer Input Resistance	16		–	3.3	–	$k\Omega$
Mixer Input Capacitance	16		–	2.2	–	pF

Pin Connection Diagram

